



DigiPoS 15" LCD Monitors

- Available with Touch Capabilities and MSR

The DigiPoS Range of LCD monitors have a rugged, flexible design which stands up to the harshest point-of-sale environments. The sleek DigiPoS 715A model has a small, retail friendly footprint.

Available in Black or Silver, this small footprint LCD has a 15.1" screen and a resolution of 1024 x 768.

Standard features of this screen are an on-screen display (OSD) with user friendly control options that allow for an automatic adjustment of the brightness, contrast, color, etc. that best suit the graphical image that is being displayed.

Designed with flexibility in mind, this LCD can be mounted for added space on the retail counter.



ADVANTAGES

- o Economical and reliable
- o Stylish Retail-Friendly, rugged design
- o Up to 1024 x 768 resolution
- o Display angle adjustable from 0 to 60 degrees
- o Built-in audio

Specifications:

DigiPoS 15" LCD Display



MODEL	715A
LCD Display	15" TFT Active Matrix Panel
Display Size	304.1 x 228.1 mm
Pixel Pitch	0.297 x 0.297 mm
Display Mode	VGA 640 x 350 (70Hz) VGA 720 x 400 (70Hz) VGA 640 x 480 (60/72/75Hz) SVGA 800 x 600 (60/72/75Hz) SVGA 1024 x 768 (60/70/75Hz) Mac. 832 x 624 (75Hz)
Max. Resolution	1024 x 768 ppi
Contrast Ratio	300
Brightness	250 cd/m ² (8mA)
Response Time	16mS (Tr + Tf) (Typ.)
Viewing Angles	+60°C ~ -60°C (L/R), +40°C ~ -60°C (U/D) (Typ.)
Display Color	16M (dithering)
Input Signal	
Video	RGB Analog 0.7V Peak-to-Peak
Sync	TTL Positive or Negative
Signal Input Connector	15 Pin Mini D-sub
On Screen Controls	Power Switch, Menu, Select (up, down), Auto Adjust
OSD	Auto-Adjustment, Contrast, Brightness, Clock, Phase, H-Position, V-Position, Color Temperature, Load default
Plug & Play	DDC1/2B
Audio System	2W per Channel
Power	Universal 90-240V, 12V/ 35W
Dimensions	375 x 357.2 x 118.2 mm (H x W x D)
Weight	4.5 Kg
Certification	FCC-B, CE, UL, TUV, TCO95